



## ZPMV8.E248803 Wiring, Printed Certified for Canada - Component

Page Bottom

### Wiring, Printed Certified for Canada - Component

See General Information for Wiring, Printed Certified for Canada - Component

SHING TECH ELECTRONICS CO LTD

E248803

303 SEC 2 NANSHAN RD

LUZHU TOWNSHIP

TAOYUAN HSIEN, 338 TAIWAN

Type	Cond Width		Cond	SS/ DS/ DSO	Max Area Diam	Max		Flame	Meets UL796 DSR	C	T
	Min	Edge				Solder	Oper				
	mm(in)	mm(in)	Thk mic(mil)	Limits C sec	Temp C	Class	I				
<b>Multilayer metal base printed wiring boards.</b>											
<b>AL02</b>	0.1 (0.004)	0.2 (0.008)	34 (1.34) Int:68	SS	50.8 (2.0)	260	10	140	V-0	All	1
<b>Multilayer printed wiring boards.</b>											
<b>AM01</b>	1.6 (0.063)	4.8 (0.189)	17 (0.67)	DS	25.4 (1.0)	260	10	130	V-0	All	-
<b>BM01</b>	0.075 (0.003)	0.10 (0.004)	17 (0.67) Int:68	DS	25.4 (1.0)	260	10	105	V-0	All	-
<b>BM02</b>	0.12 (0.005)	0.12 (0.005)	17 (0.67) Int:27	DS	25.4 (1.0)	260	10	130	V-0	All	-
<b>GM01</b>	0.10 (0.004)	0.10 (0.004)	12 (0.47) Int:102	DS	25.4 (1.0)	260	10	130	V-0	All	2
<b>GM01A</b>	0.075 (0.003)	0.075 (0.003)	12 (0.47) Int:102	DS	25.4 (1.0)	260	10	130	V-0	All	4
<b>HM01(a)</b>	0.10 (0.004)	0.10 (0.004)	12 (0.47) Int:210	DS	50.8 (2.0)	260	10	130	V-0	All	3
<b>Single layer metal base printed wiring boards.</b>											
<b>AL01</b>	0.1 (0.004)	0.2 (0.008)	34 (1.34)	SS	50.8 (2.0)	260	10	140	V-0	All	0
<b>AL01A</b>	0.1 (0.004)	0.1 (0.004)	17 (0.67)	SS	50.8 (2.0)	260	10	130	V-0	All	0
<b>AL03</b>	0.10 (0.004)	0.10 (0.004)	17 (0.67)	DS	50.8 (2.0)	260	10	130	V-0	-	0
<b>Single layer printed wiring boards.</b>											
<b>AD01</b>	1.6 (0.063)	4.8 (0.189)	17 (0.67)	DS	25.4 (1.0)	260	10	130	V-0	All	-
<b>BD01</b>	0.075 (0.003)	0.1 (0.004)	17 (0.67)	DS	25.4 (1.0)	260	10	105	V-0	All	-
<b>BD02</b>	0.12 (0.005)	0.12 (0.005)	17 (0.67)	DS	25.4 (1.0)	260	10	130	V-0	All	-
<b>GD01</b>	0.10 (0.004)	0.10 (0.004)	12 (0.47)	DS	25.4 (1.0)	260	10	130	V-0	All	2
<b>GD01A</b>	0.075 (0.003)	0.075 (0.003)	12 (0.47)	DS	25.4 (1.0)	260	10	130	V-0	All	4
<b>HD01(a)</b>	0.10 (0.004)	0.10 (0.004)	12 (0.47)	DS	50.8 (2.0)	260	10	130	V-0	All	3

(a) - For Types HD01 & HM01: Min. Cond. Width = 0.10 mm/ Edge Cond. Width = 0.10 mm for External Cu Thk = 12 ~ 102 mic; Min. Cond. Width = 0.40 mm/ Edge Cond. Width = 0.40 mm for External Cu Thk = 102 ~ 210 mic.

Marking: Company name or trademark **BBG** **SW**, or file number and type designation and the Recognized Component Mark for

Canada, **CU**. May be followed by a suffix to denote factory identification or burning test classification.

Last Updated on 2015-11-20

[Questions?](#)[Print this page](#)[Terms of Use](#)[Page Top](#)

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2016 UL LLC".