

Type	Cond Width		Min Edge mm(in)	Conduct Thk mic(mil)	SS/DS/DSO	Max Area Diam mm(m)	Solder Limits C sec	Max Oper Temp C	Flame Class	Meets UL796 DSR	C T I
	Min mm(in)	Max									
Multilayer metal base printed wiring boards.											
AL02	0.1 (0.004)	0.2 (0.008)	34 (1.34) Int68	SS	50.8 (2.0)	260	10	140	V-0	All	1
Multilayer printed wiring boards.											
AM01	1.6 (0.063)	4.8 (0.189)	17 (0.67)	DS	25.4 (1.0)	260	10	130	V-0	All	-
BM01	0.075 (0.003)	0.10 (0.004)	17 (0.67) Int68	DS	25.4 (1.0)	260	10	105	V-0	All	-
BM02	0.12 (0.005)	0.12 (0.005)	17 (0.67) Int27	DS	25.4 (1.0)	260	10	130	V-0	All	-
GM01	0.10 (0.004)	0.10 (0.004)	12 (0.47) Int102	DS	25.4 (1.0)	260	10	130	V-0	All	2
GM01A	0.075 (0.003)	0.075 (0.003)	12 (0.47) Int102	DS	25.4 (1.0)	260	10	130	V-0	All	4
HM01(a)	0.10 (0.004)	0.10 (0.004)	12 (0.47) Int210	DS	50.8 (2.0)	260	10	130	V-0	All	3
RM01	0.075 (0.003)	0.075 (0.003)	17 (0.67) Int102	DS	50.8 (2.0)	260	10	130	V-0	All	*
Single layer metal base printed wiring boards.											
AL01	0.1 (0.004)	0.2 (0.008)	34 (1.34)	SS	50.8 (2.0)	260	10	140	V-0	All	0
AL01A	0.1 (0.004)	0.1 (0.004)	17 (0.67)	SS	50.8 (2.0)	260	10	130	V-0	All	0
AL03	0.10 (0.004)	0.10 (0.004)	17 (0.67)	DS	50.8 (2.0)	260	10	130	V-0	All	0
Single layer printed wiring boards.											
AD01	1.6 (0.063)	4.8 (0.189)	17 (0.67)	DS	25.4 (1.0)	260	10	130	V-0	All	-
BD01	0.075 (0.003)	0.1 (0.004)	17 (0.67)	DS	25.4 (1.0)	260	10	105	V-0	All	-
BD02	0.12 (0.005)	0.12 (0.005)	17 (0.67)	DS	25.4 (1.0)	260	10	130	V-0	All	-
GD01	0.10 (0.004)	0.10 (0.004)	12 (0.47)	DS	25.4 (1.0)	260	10	130	V-0	All	2
GD01A	0.075 (0.003)	0.075 (0.003)	12 (0.47)	DS	25.4 (1.0)	260	10	130	V-0	All	4
HD01(a)	0.10 (0.004)	0.10 (0.004)	12 (0.47)	DS	50.8 (2.0)	260	10	130	V-0	All	3
RD01	0.075 (0.003)	0.075 (0.003)	17 (0.67)	DS	50.8 (2.0)	260	10	130	V-0	All	0

(a) - For Types HD01 & HM01: Min. Cond. Width = 0.10 mm/ Edge Cond. Width = 0.10 mm for External Cu Thk = 12 ~ 102 mic; Min. Cond. Width = 0.40 mm/ Edge Cond. Width = 0.40 mm for External Cu Thk = 102 ~ 210 mic.

* - CTI marking is optional and may be marked on the printed wiring board.

Marking: Company name or trademark, **UL** or file number and type designation. May be followed by a suffix to denote factory identification or burning test classification.

Last Updated on 2020-02-19

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from: UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"